

## KIT POMPE - SETTORE EDILIZIA PUMP KIT FOR BUILDING SECTOR

### POMPA AIRLESS ELETTRICA A PISTONE CON KIT DI VERNICIATURA AIRLESS ELECTRIC PISTON PUMP WITH PAINTING KIT

#### K7000

##### APPLICAZIONI

Ideale per lavori di edilizia pesante, lavori gravosi e continuativi.

##### MATERIALI UTILIZZABILI

Pitture intumescenti, membrane liquide, impermeabilizzanti, rivestimenti ad alto solido in volume.

##### CARATTERISTICHE TECNICHE

Controllo elettronico della pressione di lavoro, facilità di utilizzo, ridotte pulsazioni nella fase di spruzzatura, particolari interni in acciaio inox, ridotta manutenzione, grande portata.

##### APPLICATIONS

Ideal for heavy construction work, heavy and continuous works.

##### USABLE MATERIALS

Intumescent paints, waterproofing liquid membranes, high solid coatings in volume.

##### TECHNICAL FEATURES

Electronic control of the working pressure, easy to use, reduced pulsation during the spraying phase, internal details in stainless steel, reduced maintenance, big delivery.



##### DATI TECNICI

Erogazione libera:	7 lt./min
Motore:	230 V 50Hz
Potenza:	3,0 kW
Peso:	43 kg
Misura max ugello	43 µ/inch
Misura standard ugello	31 µ/inch
Pressione max macchina	200 bar
Lunghezza max tubo alta pressione	70 m

##### TECHNICAL DATA

Free flow:	1.8 gpm
Motor:	230 V 50Hz
Power:	3,0 kW
Weight:	95 lb
Max. nozzle size	43 µ/inch
Standard nozzle size	31 µ/inch
Max. operating pressure	2900 psi
Max. high pressure hose length	230 ft

ART.	CODE	Descrizione / Description
------	------	---------------------------

07770	00K	K7000 con kit di verniciatura 3,0 kW / K7000 with painting kit 3,0 kW
-------	-----	---

##### COMPOSIZIONE KIT / KIT COMPOSITION:

K7000 pompa con sistema di aspirazione e ricircolo / K7000 pump with suction and recirculation system

Tubo alta pressione Ø 3/8", lunghezza 10 m, raccordo 16x1,5 FG / Ø 3/8" high pressure hose, 33 ft length, 16x1.5 FG fitting

Pistola K90, raccordo 16x1,5 M, 250 bar / K90 spray gun with 16x1.5 M fitting, 3625 psi

Autopulitore MKII Speedy con ugello SP varie misure (vedi tabella pag. 57)

MKII speedy self-cleaning reversible tip with SP nozzle various size (see table page 57)

Raccordo con manometro 16x1,5 MF Inox / Stainless steel fitting with pressure gauge 16x1.5 MF